

## THE CUTTING EDGE OF SIMPLICITY

InstroTek's MC3 Elite™ is an advanced, yet easy to operate moisture density gauge designed for all operators ranging from new technicians to those with advanced density testing experience. The MC3 Elite is the result of over 40 years of testing experience, and is constructed to withstand rugged, construction testing environments. It features a simple operator interface, **NEW** large backlit LCD display, illuminated keypad, precision machined base and is designed with reliable, surface-mount electronics. All InstroTek / CPN gauges are backed by unmatched reliability, technical support and low maintenance costs.

The MC3 Elite is loaded with simple, user friendly functions. Density, moisture and other required field parameters are automatically calculated and displayed and can be stored under specific user-designed projects. The data can be easily downloaded to a computer, printer or written to a USB flash drive. The gauge is equipped with a reliable, non-contact magnetic depth indicator and state-of-the-art moisture resistant electronics. The battery pack is designed to provide weeks of operation and is integrated with a 9V battery for backup. The mechanical design includes a machined, aluminum base and a rugged, polycarbonate topshell designed to withstand the demands of the toughest construction and testing environments.

Ask us about **NukeTrack™ Nuclear Gauge Tracker** now available for the MC3 Elite! Locating your gauge has never been easier!

Now available with **NukeTrack™**  
Nuclear Gauge Tracker!



Mobile App for



# MC3 ELITE™

### An advanced gauge with improved functions:

Meets ASTM D6938, D2950, D7013, D7759, C1040 and AASHTO T310

- ▶ **NukeTrack™** Nuclear Gauge Tracker (*optional*)
- ▶ Mobile App reporting for any Android® or Apple® Smartphone or Tablet
- ▶ GPS for Accurate Measurement Location
- ▶ Bluetooth
- ▶ USB Storage
- ▶ Project Storage
- ▶ Memory/Storage of Results
- ▶ Software Updates via USB Drive
- ▶ Alphanumeric Keypad
- ▶ Large 4 line X 20 character LCD Display with 3/8" (9mm) Tall Characters
- ▶ Backlit LCD and Keypad
- ▶ 9V Alkaline Battery Backup
- ▶ Gauge Case with Wheels

### SPECIFICATIONS

Standards	ASTM D6938, D2950, D7013, D7759, C1040 and AASHTO T310
Density Measurement Range	70 to 170 pcf (1.120 to 2.73 gcc)
Moisture Measurement Range	0 to 40 pcf (0 to 0.64 gcc)
Density Source	Cesium 137
Moisture Source	Americium 241: Beryllium
Density Source Activity	Maximum (10 mCi) 370 Mbq
Moisture Source Activity	Maximum (50 mCi) 1.85 GBq
<b>PRECISION</b>	
BS one-minute test	±0.50 pcf (0.008 gcc)(at 125 pcf)
Transmission one-minute test	±0.25 pcf (0.004 gcc)(at 125 pcf)
Moisture one-minute test	±0.25 pcf (0.004 gcc)(at 10 pcf)
<b>CHEMICAL COMPOSITION ERROR</b>	
Backscatter	±1.00 pcf (0.016 gcc)
Transmission	±0.75 pcf (0.012 gcc)
<b>SURFACE ROUGHNESS ERROR (0.05 in. 100% void)</b>	
Backscatter	- 4.00 pcf (0.064 gcc)
Transmission	- 0.50 pcf (0.008 gcc)
<b>OPERATING TEMPERATURE</b>	
Ambient	- 14° to 167°F (-10° to 75°C)
Surface	Up to 350°F (175°C)
Power Source	6-Cell AA NiMH battery pack with a single 9V alkaline for backup
Battery Life	500-1000 recharge/discharge cycles
Display	Large 4 line X 20 character LCD display with 9mm tall characters
Memory Storage	10 Projects with 40 readings each
Gauge Size	26.7" H X 14.1" W X 9.8" D (67.8 x 35.8 x 24.8cm)
Weight	28.5 lbs (13 kg)
Shipping Weight	90 lbs (40.82 kg)



**Stuart Hunt**  
& Associates Ltd.

📍 Central Canada | 5949 Ambler Dr, Mississauga ON, L4W 2K2  
 📍 Western Canada | 15803 - 145 Avenue NW, Edmonton AB, T6V 0H8  
 ✉ sales@stuarthunt.com ☎ +1 (800) 661-4591 🌐 www.stuarthunt.com