Hand/Foot Contamination Monitor



Model HFC-8

Robust and Portable Hand-Foot-Clothing Monitor with Touch-Screen Display

The Model HFC-8 is a compact hand, foot, and clothing monitor to measure personnel leaving controlled areas. Robust, with a removable probe and spring-loaded hand detectors, the Model HFC-8 is designed for portability between different areas. Featuring a detector arrangement to measure hands and feet in one measurement step, the Model HFC-8 integrates the latest technology and design, while meeting Industry and regulatory standards

The standard unit consists of:

- 8 beta plastic detectors with semiconductor readout, one hand detector is a removable probe
- · Robust stainless-steel housing
- · Ergonomic detector positioning
- Integrated 12 in. touch-screen display
- Fully automated measurement process with audiovisual user guidance
- Latest industry-controller technology
- Power provided by UPS for measurements during power outages



Key Benefits

- Intuitive User-Friendly Software
- Spring-Loaded Hand Detectors for Reliable Contact with the Hand Surfaces
- Compact Footprint with Easy Access to the Service Cabinet
- Modern Touch-Screen Display
- Stainless Steel Housing for Easy Cleaning and Durability
- · Access to Historical Measurement Data via Integrated Database
- Export of Measurement/Parameter Data in XML Format via USB
- Remote Access via Web Browser Interface



Hand/Foot Contamination Monitor



Standards:	The Monitor is compliant with the following Standards: IEC61098, ISO11929, CE, CSA / UL, EMC directive,
Detectors:	8 beta plastic detectors
	Active area (per measurement): 2,400 cm ² (372 in ²)
User Software:	Fully automated measurement process with voice
	guidance for users. Web based for remote RPO access.
Electronics:	Touch-screen industry-controller incl. network
	connection
Housing:	Stainless steel
	Service-door from the front
Sensors:	2x hand and 2x foot sensors
	One hand-detector removable as probe
Ext.	1,493mm x 642mm x 710 mm (58.8 x 25.3 x 30 in.)
Dimensions:	(H x W x D)
Weight:	60 kg (133 lb)
Power Supply:	External Power Supply 100-240V 1.6A MAX / 24V- 5A
	Output



Touch-Screen Display



Spring-Loaded Hand-Detectors



Removable Hand-Detector

Additional Options

Ludlum GmbH offers a range of additional options to enhance the capabilities of the monitor:

- Alpha/Beta discrimination by ZnS detectors
- Gas-flow detectors
- Various configurations e.g. card reader connection, lights, interfaces, etc.

